



Bulletin Number: 88-3-17  
 Reference Number: 833503  
 Publish Date: 3/88

PONTIAC DIVISION

'88



Dealer  
 Service  
 Bulletin



**Subject:** COATED WHEEL WEIGHTS FOR ALUMINUM WHEELS

**Models Affected:** 1988 FIERO

All aluminum wheels must be balanced using the nylon coated weights to prevent damage to the clear coat finish.

These balance weights provide a much better appearance and are used on both the outboard and inboard rim flanges. They will not discolor, corrode or damage the wheel as may have been the case in the past with some uncoated clip-on weights used on aluminum wheels.

Below is a complete list of all the coated weights required for balancing Fiero aluminum wheels.

<u>Weight</u>	<u>Part Number</u>
1/2 Oz.	9591582*
3/4 Oz.	9591583*
1 Oz.	9591361
1-1/4 Oz.	9591362
1-1/2 Oz.	9591363
1-3/4 Oz.	9591364
2 Oz.	9591365
2-1/4 Oz.	9591366
2-1/2 Oz.	9591367

\* The 1/2 and 3/4 Oz. weights are new. They have a new retention clip.

When installing the coated weights, care must be taken so that the nylon coating does not crack. It is recommended that a teflon hammer be used, such as 85403 Nicholson Industrial hammer, available through the Charles Strelinger Company, Warren, Michigan (313)-268-4100, or equivalent.

SERVICE DEPARTMENT  
 PONTIAC DIVISION  
 GENERAL MOTORS CORPORATION

Pontiac bulletins are intended for use by professional technicians, NOT a "do-it-yourselfer." They are written to inform these technicians of conditions that may occur on some vehicles, or to provide information that could assist in the proper service of a vehicle. Properly trained technicians have the equipment, tools, safety instructions, and know-how to do a job properly and safely. If a condition is described, DO NOT assume that the bulletin applies to your vehicle, or that your vehicle will have that condition. See your Pontiac dealer for information on whether your vehicle may benefit from the information.

Read, Initial & Pass On

• Service Supervision

• Parts

• Accounting